N-Driver™

Thermal Imaging Driving Assistant System



N-Driver[™] sees through the total darkness, thick smoke, dense fog, heavy rain and snow, reveals unexpected obstacles, highlights sudden events, improves visibilities of road signs, navigates on unknown roads and overcomes blindness caused by oncoming headlights, thus dramatically lowers the risks of driving and enhances the safety of lives, properties and profits.

Featured razor-sharp live imaging, extremely wide viewing range, incredible durability in diverse harsh environments, instant installation on any vehicles and high affordability for any limited budgets, N-Driver TM is absolutely the perfect choice of driving assistant vision systems.

Features and Benefits

Rugged and compact design ensures easy integration
Short response time & high refreshing frequency
NUC-free IR images with high quality during the whole driving process
Wide-angle lens delivers super-wide viewing range
Enabling a detection range 4 times further than traditional headlight
Hermetically sealed water & dust proof





	N-Driver™
Imaging Performance	
Detector Type	Microbolometer UFPA 384×288, 25 μ m
Spectral Range	8 to 14 μ m
Field of View	40.5° ×31°
Focus/Min Focusing	13mm lens, 1m
Image Frequency	50Hz PAL/60Hz NTSC
Video	
Output	RS170 PAL /NTSC composite video
Connector Type	LEMO-HGGOB309/FGGOB309 plug
Power	
Input Voltage	12V DC±3V DC
	12V DC±3V DC 3W
Input Voltage	
Input Voltage Power Dissipation	
Input Voltage Power Dissipation Environmental Specifications	3W
Input Voltage Power Dissipation Environmental Specifications Operating Temperature Range	3W -10℃ to +55℃
Input Voltage Power Dissipation Environmental Specifications Operating Temperature Range Storage Temperature Range	3W -10℃ to +55℃ -40℃ to +60℃
Input Voltage Power Dissipation Environmental Specifications Operating Temperature Range Storage Temperature Range Encapsulation	3W -10℃ to +55℃ -40℃ to +60℃



IR Image







